

The testing simulated real life use of the equipment. The saw with proper vacuum were tested under conditions that would produce a maximum cut depth of 3 inches. The sampling demonstrated that the equipment, when used according to manufacturer's recommendation, will perform as designed to eliminate respirable dust and respirable crystalline silica.

Narrative:

Diamond Products First-Cut[™] CC190PRO-EE with skid plate, vacuum side cover and Core Vac[™] CV1900 vacuum were tested. The First-Cut[™] CC190PRO-EE early entry green walk-behind concrete saw is powered by a 20.8HP Honda® GX630 engine. Flat sawing was accomplished on green concrete at a total length of 36-inches. A 14-inch First-Cut[™] Expert blade was used at a cutting depth of 3-inches. The testing was done without water.

Respirator protection is recommended but not required when the equipment is used properly and according to manufacturer's recommendations.

| Product: | CC190PRO-EE First-Cut [™] Early Entry Saw with Core Vac [™] CV1900 Vacuum |
|----------------------|---|
| Engineering Control: | Core Vac™ CV1900 Vacuum |
| Test Action: | Flat saw cutting |
| Test Material: | Green concrete less than 3 hours after pour |
| Test Method: | Personal sampling; dust track area sampling |

| | CC190PRO-EE with CV1900 Vacuum Sample Data | | | | | | | |
|------------------|--|-------------------|-------------|----------------|---------------|--------------|--------------------------------|--|
| Sampling Date | Time of Sample | Sampling Duration | Type of Cut | Blade Diameter | Length of Cut | Depth of Cut | Weather Conditions | |
| January 25, 2018 | 10:09 AM | 22 Minutes | Flat Sawing | 14" | 36" | 3" | Outside, Sunny 61 ^o | |

| | SiO2 | Below Detection Limits | |
|----------------------|-----------------|------------------------|-------------------|
| SAMPLING RESULTS: | Respirable Dust | Below Detection Limits | For further infor |
| RESULIS. | Total Dust | 011 mg/m3 | Product |

Testing conducted by SCT, Inc.

For further information, please contact Diamond Products Health and Safety Department.

This Objective Data represents one test per application and the amount of work performed during the Sampling Duration. The results provide the respirable silica dust exposure level based on the specific testing conditions, and in specific case situations.



Diamond Products Limited 333 Prospect Street - Elyria, OH 44035 U.S.A. Phone: 800-321-5336, Fax: 800-634-4035 diamondproducts.com



Safety Engineering * Consultation * Training 6993 Pearl Rd. Middleburg Heights, OH 44130 800-204-1729