

WSE2226 High Cycle Wall Saw System Complete

Quick Mount

- · Quick mounting blade flanges make easy removal of blade
- Up to 40" maximum starter blade without being in the cut
- Feed with Worm Drive System
- Self-locking-no brake necessary

Product Details

· Improved seals

2 Handles

- Quick disconnect with 2 handles for fast removal and set up 2-stage gear box
- Largest ø range in the industry (ø 32" to 86")
- Safety clutch in front of gear box for better protection
- · Simple re-engage lever in case of blade jams

Specifications:

BLADE

Maximum cutting depth 39"

Maximum blade capacity 86"

Blade size over 60" in diameter requires 60mm flange system (Included with package)

Maximum starter blade size 40"

Blade mount Quick-release flange

DESIGN

Infinitely adjustable swivel arm rotates 360°

2 carrying handles with locking function

MOTOR

Water cooled high frequency motor with 2 speed gearbox

Output at 63 amp 26 kW, 35 HP

POWER PACK/INVERTER INPUT

Voltage 460 Volt

Frequency 50Hz/60 Hz

Output Frequency 400 Hz

WEIGHT

1/2

Product Details



https://www.diamondproducts.com/hydrostress-wse2226-3824

Wall Saw WSE2226 including feed motors-without main drive blade motor 66 lbs.

Electric main blade motor only-detachable 53 lbs.

MINIMUM GENERATOR

SIZE REQUIREMENT 50kW



• Model Group: HYDROSTRESS

• Model Number: HYDROSTRESS WSE2226

Catalog Number: 46473
Part Number: 5801534
Engine/Motor Make: No
Engine/Motor Model: No

• Sawing Engine/Motor Model: No

• Motor/Engine Power: No

Power Source: NoPower Source: NoBlade Capacity: No

2/2