

C7574DD-PRO IN-LINE WALK BEHIND SAW

Features & Benefits:

- Tier 4 Final Deutz® diesel engine
- Available with enhanced clutch assembly that allows the blade to be disengaged while the engine is running (single speed only)
- Easy maneuvering self propelled drive
- · Strongest frame on the market
- · Hydraulic wheel motor drive
- Blade shaft gearbox-oil bath for low maintenance
- 4 stage air filter system
- 19-3/4" maximum cutting depth
- Maintenance-free DVERT® diesel oxidation catalytic converter (DOC-only, no DPF).
- High pressure common rail electronic fuel injection.
- Modern computer interface engine controls 20"-48" Blade Capacity

Specifications:

7-1/4" (5" flange) Maximum depth of cut with 20" blade: Maximum depth of cut with 26" blade: 10-1/4" (5" flange) Maximum depth of cut with 30" blade: 12-1/4" (5" flange) 14-3/4" (6" flange) Maximum depth of cut with 36" blade: Maximum depth of cut with 42" blade: 17-1/4" (7" flange) Maximum depth of cut with 48" blade: 19-3/4" (8" flange) Engine: Deutz® Turbo Diesel **Engine Specs:** 4 Cylinder, 3.3 Liter Max Engine Power: 74.3HP at 2,600 RPM Power at the Blade Shaft: 74 Horsepower

Emission Regulation: EPA Tier 4 Final Compliant

Blade shaft diameter:

Arbor size:

Blade shaft bearings: Multiple ball bearings in oil bath

20 V-belts Blade shaft drive: Blade mounting:

Right or Left Electro-hydraulic pump Blade raise & lower: Blade Coolant: Dual multi-spray tubes

Drive speed: 0-250 feet/min forward and reverse Transmission: Hydro pump powering dual wheel motors

2"

1" w/drive pin

Air filter: 4 stage w/restriction indicator

Fuel capacity: 9 gallons

1/2





Size	Part Number	Catalog Number
	5801640	112298
	5801641	112299
	5801642	112300
	5801643	112301
	5801644	112302
	5801645	112303
	5801652	112310
	5801653	112311
	5801654	112312
	5801655	112313

2/2