CC7574DKV IN-LINE WALK BEHIND SAW

Features & Benefits:

- Stage 5 Kubota® diesel engine
- Self-propelled Eaton Model 10 transmission
- Available with enhanced clutch assembly that allows the blade to be disengaged while the engine is running (single speed only)
- Strongest frame on the market
- · Hydraulic wheel motor drive
- Blade shaft gearbox-oil bath for low maintenance
- High pressure common rail electronic fuel injection.
- Modern computer interface engine controls
- 20"-48" Blade Capacity

Specifications:

Maximum depth of cut with 20" blade: 7-1/4" (5" flange) Maximum depth of cut with 26" blade: 10-1/4" (5" flange) Maximum depth of cut with 30" blade: 12-1/4" (5" flange) Maximum depth of cut with 36" blade: 14-3/4" (6" flange) Maximum depth of cut with 42" blade: 17-1/4" (7" flange) 19-3/4" (8" flange) Maximum depth of cut with 48" blade: Engine: Kubota® Turbo Diesel **Engine Specs:** 4 Cylinder, 3.3 Liter Max Engine Power: 74.5HP at 2,600 RPM Power at the Blade Shaft: 70 Horsepower

Emission Regulation: EPA Stage 5 Compliant

Blade shaft diameter:

Arbor size:

Blade shaft bearings:

Multiple ball bearings in oil bath
Blade shaft drive:

20 V-belts-4 power bands

Blade mounting: Right or Left
Blade raise & lower: Electro-hydraulic pump

Blade Coolant: Dual multi-spray tubes

Drive speed:

Transmission:

0-250 feet/min forward and reverse
Hydro pump powering dual wheel motors

2"

1" w/drive pin

Air filter: 4 stage w/restriction indicator

Fuel capacity: 9 gallons

1/2





Size	Part Number	Catalog Number
	5801460	106338
	5801461	106339
	5801462	106340
	5801463	106341
	5801464	106342
	5801465	106343
	5801466	106344
	5801467	106345
	5801468	106346
	5801469	106347
	5801470	106348
	5801471	106349
	5801472	106350
	5801473	106351
	5801474	106352
	5801475	106353

2/2