



CG3R Pavement Groover


FEATURES:

- Riding unit for grooving long areas of pavement
- Compact and highly maneuverable
- Robust construction and heavy duty design
- On-board slurry vacuum & discharge system
- 30" (77.2cm) grooving width
- Uses standard 5" (12.7cm) bore 12" (30.48cm) diameter blades
- Joystick speed control with integral raise/lower switch
- Full compliment of work lights for night jobs

SPECIFICATIONS:

Engine	Deutz Turbo Diesel 2.9L, 74.9HP Tier 4 Final, EU Stage V
Dimensions	Length 87-5/8" (222.57cm), Width 54-1/8" (137.48cm), Height 87-7/8" (223.2cm)
Weight	3200 lbs. (1451.5Kg) Estimated
Fuel Capacity	25.85 Gallons (97.85 liters)
Blade Shaft	5" (12.7cm) Diameter with 4-draw Bolts
Blade Diameter	12" (30.48cm)
Cutting Width	30" (76.2cm)
Blade Shaft RPM	13000 Maximum
Blade Shaft Drive	Belt Driven
Hydraulics	Electric/Hydraulic Blade Raise/Lower
Ground Drive	Joystick-controlled Belt Driven Closed Looped Hydrostatic Pump
Vacuum System	Hydraulically-driven Fan and Self Priming Centrifugal Slurry Pump
Electrical	12 Volt
Speed	Up to 250 Feet Per Minute Forward/Reverse
Machine Controls	Power Steering, Joystick Ground Drive Control with Integral Head Raise/Lower Switch

Part Number: CG3R, Catalog # 99357



Product Details

<https://www.diamondproducts.com/cg3r-pavement-groover>



- **Model Group:** No
- **Model Number:** No
- **Catalog Number:** No
- **Part Number:** No
- **Engine/Motor Make:** No
- **Engine/Motor Model:** No
- **Sawing Engine/Motor Model:** No
- **Motor/Engine Power:** No
- **Power Source:** No
- **Power Source:** No
- **Blade Capacity:** No